

PRODUCT-DETAILS

PSTX720-600-70

PSTX720-600-70 Softstarter



Información General

Global Commercial Alias	PSTX720-600-70
Tipo de producto extendido	PSTX720-600-70
Código de producto	1SFA898118R7000
ABB Type Designation	PSTX720-600-70
EAN	7320500510384
Descripción corta	PSTX720-600-70 Softstarter
Descripción larga	Softstarter PSTX720-600-70 for max 600V main voltage and 100 - 250V 50/60Hz control supply voltage.

Clasificación

Cantidad mínima de pedido	1 piece
Código arancelario	85044090

Descargas Populares

Ficha técnica, información técnica	1SFC132012C0201
Instrucciones y manuales	1SFC132081M0201

Dimensiones

Ancho del product	435 mm
Alto del producto	493 mm
Largo del product	369 mm
Peso del product	46.5 kg

Technical

Rated Operational Voltage	208 ... 600 V AC
Rated Control Supply Voltage (U _s)	100 ... 250 V AC
Rated Control Circuit Voltage (U _c)	DC Operation 24 V
Rated Frequency (f)	50/60 Hz Main Circuit 50 / 60 Hz
Rated Operational Power - In-Line Connection (Pe)	(230 V) 200 kW (400 V) 400 kW (500 V) 500 kW
Rated Operational Current - In-Line Connection (Ie)	720 A
Rated Operational Power - Inside Delta Connection	at 230 V 355 kW at 400 V 710 kW at 500 V 880 kW
Rated Operational Current - Inside Delta Connection	1247 A
Service Factor Percentage	100 %
Overload Protection	Built-in electronic overload protection
Integrated Electronic Overload	Yes
Adjustable Rated Motor Current Ie	30 ... 100 %
Starting Capacity at Maximum Rated Current Ie	4xIe for 10s
Ramp Time	1 ... 120 second [unit of time]
Initial Voltage During Start	10 ... 99 %
Step Down Voltage Special Ramp	100 ... 10 %
Current Limit Function	1.5 ... 7.5 xIe
Switch for Inside Delta Connection	Yes
Run Signal Relay	Yes
By-pass Signal Relay	Yes
Fault Signal Relay	Yes
Overload Signal Relay	Yes
Analog Outputs	0...10 V, 0...20 mA, 4...20 mA
Signal indication ready to start/standby ON (LED)	Green
Signal indication running R (LED)	Green
Signal indication protection (LED)	Yellow
Signal indication fault (LED)	Red
Communication	Built in Modbus interface, Anybus, FieldBusPlug (with adapter).
Grado de protección	IP00
Terminal Type	Main Circuit: Bars
Connecting Capacity Control Circuit	Rigid 1 x 2.5 mm ²
Connecting Capacity	Rigid 1 x 2.5 mm ²

Supply Circuit

Tightening Torque	Main Circuit 45 N·m
Product Main Type	PSTX720

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V
Ampere Rating UL/CSA	720 A
Tightening Torque UL/CSA	Main Circuit 398.3

Ambiente

Temperatura ambiente	Funcionamiento -25 ... +60 °C Almacenamiento -40 ... +70 °C
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Certificados y Declaraciones (Número de Documento)

CQC Certificate	CN: CQC2015010304830300 / SE: CQC2015010304830295
Declaration of Conformity - CCC	CN: 2020980304001095 / SE: 2020980304001491
Declaración de conformidad - CE	2CMT005209
Environmental Information	2CMT005232
Instrucciones y manuales	1SFC132081M0201
RoHS Information	2CMT005210

Información de Embalaje

Embalaje Nivel 1 Ancho	600 mm
Embalaje Nivel 1 Largo	616 mm
Embalaje Nivel 1 Alto	800 mm
Embalaje Nivel 1 Peso	58.5 kg
Embalaje Nivel 1 EAN	7320500510384
Embalaje Nivel 1 Unidades	box 1 piece

Clasificaciones

Object Classification Code	Q
ETIM 4	EC002572 - Electronic motor control and protection device
ETIM 5	EC002572 - Electronic motor control and protection device
ETIM 6	EC002572 - Motor management device
UNSPSC	39121521

Categorías

Convertidores de frecuencia → Softstarters → Arranadores suaves → PSTX Softstarters → PSTX720

Productos y sistemas de baja tensión → Aparatos de control → Softstarters → Arranadores suaves → PSTX Softstarters → PSTX720

