

PRODUCT-DETAILS

DB 4020

AL HTYPE COMP CONN 2-3/16IN 6CONN



General Information	
Extended Product Type	DB 4020
Product ID	7TAA263750R0003
EAN	0783786717163
Catalog Description	AL HTYPE COMP CONN 2-3/16IN 6CONN
Long Description	Aluminum H-Tap Compression Connectors, length 2-3/16 inch, die D. 6 Connectors
Ordering	
EAN	0783786717163
Customs Tariff Number	8536904000
Dimensions	
Product Net Weight	.148 lb 67.12 g
Container Information	
Package Level 1 Units	25 piece
Package Level 1 Width	2.4 in 61 mm
Package Level 1 Height	5.1 in 130 mm

783786717163

Package Level 1 Depth / Length	13 in 330 mm
Package Level 2 Units	250 piece
Package Level 2 Width	13.2 in 335 mm
Package Level 2 Height	11.7 in 297 mm
Package Level 2 Depth / Length	14 in 356 mm

Additional Information	
Application	For Combinations of Aluminum to Aluminum and Aluminum to Copper Conductors.
Brand / Label	Blackburn
Connection Type	Compression
Insulation Material	None
Material	Aluminum
Mounting Type	None
Number of Batteries	0
Number of Conductors	2
Product Name	ELECTRICAL CONNECTOR <1000V
Product Type	Aluminum Wide-Range Aluminum Tap Connectors
Size	Length 2-3/16 inches
Special Functions	Made of 1350 Aluminum Alloy for high strength and high conductivity. Standard Compression tools and dies install all sizes - no special tools needed. Field-proven ribbed design enables excellent connector/conductor contact without distorting the conductor's shape. Fold-in tabs provide tab interlock as tool closes. Prefilled with oxide inhibitor held captive in the rib/connection area.
Standards	RUS Accepted. Complies with ANSI C119.4 Specifications
Surface Finishing	Bare
Temperature Range	up to 90 °C

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	DB 4020
Instructions and Manuals	DB 4020

Classifications

UPC

UNSPSC	39121409
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category	4543 >> Wire connectors

Categories

DB 4020 3

